

# SMT Shielded Power Inductors GSSLF6028

## Features (特長)

- Magnetically shielded construction (閉磁路構造設計)
- Compact and thin (輕便薄小)
- Large Current and Low DCR (大電流低直流阻抗)

## Applications (用途)

- Computers, DC/DC converter, VCR Camera. (電腦、直流轉換器、攝影機)



## Product Identification (產品識別)


**GSSLF6028** - \_\_\_\_ \_\_\_\_ (Ex. GSSLF6028-100M)

1            2            3

1. SMT Shielded Power Inductors (閉磁式功率電感) (GSSLF6028)
2. Inductance (電感值)
3. Tolerance (誤差值) ( 參照表 K 10%, L 15%, M 20%, N 30% )



## Configurations & Dimensions (結構圖及規格尺寸)



Unit In mm

Type (型式)	A (max)	B (max)	C (max)	D ±0.2	E (max)	F	G	H
GSSLF6028	6.2	6.2	3.0	1.8	3.0	2.2	2.0	2.5

✦ Design as Customer's Requested Specifications. (可依客戶特殊需求設計)

# SMT Shielded Power Inductors

## GSSLF6028

Electrical Characteristics for GSSLF6028 Series [GSSLF6028 系列電子特性規格]

Part Number 產品料號	Inductance ( $\mu$ H) 電感值 (L)	Test Freq. ( KHz ) 測試頻率	DCR ( $\Omega$ ) (max) 直流阻抗	IDC (A) (max) 定格電流
GSSLF6028-100M	10.00	1	0.150	1.10
GSSLF6028-120M	12.00	1	0.200	1.00
GSSLF6028-150M	15.00	1	0.230	0.90
GSSLF6028-180M	18.00	1	0.270	0.80
GSSLF6028-220M	22.00	1	0.340	0.74
GSSLF6028-270M	27.00	1	0.380	0.66
GSSLF6028-330M	33.00	1	0.450	0.59
GSSLF6028-390M	39.00	1	0.490	0.54
GSSLF6028-470M	47.00	1	0.690	0.50
GSSLF6028-560M	56.00	1	0.780	0.46
GSSLF6028-680M	68.00	1	1.070	0.42
GSSLF6028-820M	82.00	1	1.210	0.38
GSSLF6028-101M	100.00	1	1.390	0.34
GSSLF6028-121M	120.00	1	1.900	0.31
GSSLF6028-151M	150.00	1	2.180	0.28
GSSLF6028-181M	180.00	1	2.770	0.26
GSSLF6028-221M	220.00	1	3.120	0.23
GSSLF6028-271M	270.00	1	4.380	0.22
GSSLF6028-331M	330.00	1	4.940	0.19

※Test Freq. : 1KHz / 0.25V.

※Operating Temp. : -40°C ~ +85°C

※Inductance drop=10% typ. at IDC.